

Megatouch Force 2005.5 Instructions

Precautions

Follow these instructions at your own risk. These instructions worked for me, but cannot guarantee the same outcome for others, or that there will be no issues at a later point in time due to the tampering of system files (eg: in-game security checks, maintenance checks, etc). These instructions are also slightly more complex than those for versions 2006 and up.

The instructions require running with administrator privileges; typos when following instructions can cause serious negative effects, resulting in the machine unable to boot the game or boot at all. ***It is strongly recommended you either***

1. Follow these instructions with a fresh installation on a separate hard drive.
2. Have the DVD installation media ready to use in case the machine goes into an unbootable / unplayable state.
3. Make a backup of the hard drive before starting (eg: plug the drive into another computer and backup via a tool such as [CloneZilla](#)).

Prerequisites

Unlike instructions for years 2006 and up, not all the steps here can be done with a USB keyboard. ***A PS/2 keyboard is needed, or a USB to PS/2 adapter!*** Otherwise, you will not be able to enter commands in the terminal when a graphical environment is brought up. In my experience, only a low-powered wired USB keyboard worked when using a USB to PS/2 adapter.

Gaining Root Privileges

Unlike the software from 2007 up, this version has two separate accounts - "root" and "maxx". Furthermore, "maxx" has user/group id 100, which is not root. The password of root is not the same as "maxx", so we're unable to log into root. However, we can gain root privileges by doing the following:

1. On machine startup, hold "alt" until you get to a red bootloader screen, then enter the following command:

```
linux init=/bin/sh
```
2. Once you have access to the terminal ("sh-2.04#" shows), make sure you're following the right instructions by checking the binary.

```
md5sum /usr/local/bin/start  
# Should return 3b8a83c9c017f942bab32f5eb079d1be
```
3. Change the user and group id of "maxx" to root by entering the following commands:

```
mount -n -o rw,remount /
```

```
cp /etc/passwd /etc/passwd.bak # Keep a backup.
sed 's/100:100/0:0/g' /etc/passwd.bak > /etc/passwd
sync
/sbin/shutdown -h -n now
```

4. Reboot the machine by pressing ctrl + alt + delete. If this does not work, manually shutdown the computer.

Obtaining access to the shell

1. Turn the machine back on, and hold “alt” until you get to the bootloader screen, then enter the following command:

```
linux 3
```

2. When prompted to login, use user “maxx” and password “maxx”.

Obtaining the game code

Similar to the [2011 instructions](#), the main binary is encrypted in a wrapper binary. We need to decrypt the main binary and replace the wrapper binary with it.

1. Make the hard drive writable:

```
mount -n -o rw,remount /
```

2. Set up the machine so that on sequential boots a graphical environment is loaded with a terminal (this is needed for upcoming steps):

```
cp ~/.xinitrc ~/.xinitrc.bak # Keep a backup.
echo -e "mount -n -o rw,remount /\nxterm" | cat - ~/.xinitrc.bak > ~/.xinitrc
```

3. Patch the wrapper binary to not delete the main binary once executed:

```
cp /usr/local/bin/start /usr/local/bin/start.bak # Nice to keep a backup.
perl -e 'print "\x90" x 5' | dd bs=1 count=5 seek=3952 of=/usr/local/bin/start conv=notrunc
md5sum /usr/local/bin/start
# Should return 160a14ca5187c165c7c12a82ee95e704
```

4. Run the game. After a few seconds, the machine should hang at a black screen.

```
/usr/local/bin/start
```

5. Wait about 10-20 seconds on the black screen, restart the machine. It will automatically boot into a terminal in a graphical environment.

6. Replace the wrapper binary with the main binary.

```
cp /tmp/dstart /usr/local/bin/dstart.bak # Nice to keep a backup.
cp /tmp/dstart /usr/local/bin/start
chmod 4755 /usr/local/bin/start
md5sum /usr/local/bin/start
# Should return 220872589f6ea7a29ed7ec2672a3820f
```

Extract the encrypted data from your actual key

1. Start the binary in debugging mode.

```
gdb /usr/local/bin/start
```

2. The debugger will hang due to SIG32 signals coming in. Issue the following command to prevent these hangs.

```
handle SIG32 nostop
```

3. Setup a breakpoint in USBIO::USBReadKeyData after key data is read in. Then dump the contents of the key into a “/.key” file.

```
break *0x828e194
command 1
dump memory /.key $ebp-0x148 $ebp-0x5c
continue
end
```

4. Unlike the instructions from 2006 and up, the key data alone is not enough to store to file. There is a 4-byte “decryption key” that needs to be stored alongside the key’s data, otherwise the program will fail to properly decode the data. Store this decryption key into a “/.decrypt” file.

```
break *0x828e2a9
command 2
dump memory /.decrypt $edx+0x380 $edx+0x384
continue
end
```

5. Run the program in debugging mode.

```
run
```

6. The machine will either boot up to the games menu, or hang on the loading screen. Either way, wait about a minute then restart the machine.

Confirming key data and decryption key

Let's make sure the data was properly saved to file. Check that the `/.key` file was made.

```
wc -c /.key
```

The output of the above command should be `236 /.key`.

Check the contents of the `/.decrypt` file.

```
hexdump /.decrypt
```

The output should look something like the following (instead of `1122 3344`, you should see random-ish characters, like `7b8f 7a62`):

```
00000000 1122 3344
00000004
```

If either the “`wc`” or “`hexdump`” commands give a `No such file or directory` error, you'll need to rerun all commands in the previous section, starting with `gdb /usr/local/bin/start`. Even if you have one of the files, you'll need to repopulate both (as their outputs are different with each run of `gdb`).

Patching `USBIO::USBConfirmKeyId()` to always return “OK” or “Success”

This method checks that the serial was read from the security key properly. Let's hardcode this method to always return a success.

```
perl -e 'print "\x31\xC0\x40\xC3"' | dd bs=1 count=4 seek=2381968 of=/usr/local/bin/start conv=notrunc
```

Patching `USBIO::USBReadKeyData()` to read the key data from disk

We need a function that can read the contents of the `/.key` file and load it into the proper memory location. Let's add this method right after the patched `ConfirmKeyId` method (note: each command from “`perl`” to “`conv=notrunc`” can be run on a single line, the `\` character is used to split up a command across multiple lines):

```
perl -e 'print "\x60\x31\xC0\xB0\x05\xBB\xCC\xDF\x28\x08"' | \
dd bs=1 count=10 seek=2383772 of=/usr/local/bin/start conv=notrunc
```

```
perl -e 'print "\x31\xC9\xCD\x80\x74\x04\x53\x6E\x6F\x42"' | \
dd bs=1 count=10 seek=2383782 of=/usr/local/bin/start conv=notrunc
```

```
perl -e 'print "\x89\xC3\xB0\x03\x8D\x8D\xB8\xFE\xFF\xFF"' | \
dd bs=1 count=10 seek=2383792 of=/usr/local/bin/start conv=notrunc
```

```
perl -e 'print "\xBA\xEC\x00\x00\x00\xCD\x80\xB0\x06\xCD"' | \  
dd bs=1 count=10 seek=2383802 of=/usr/local/bin/start conv=notrunc
```

```
perl -e 'print "\x80\x61\x68\xD0\xE0\x28\x08\xC3"' | \  
dd bs=1 count=8 seek=2383812 of=/usr/local/bin/start conv=notrunc
```

```
perl -e 'print "\x2F\x2E\x6B\x65\x79\x00\x00"' | dd bs=1 count=7 seek=2383820 of=/usr/local/bin/start  
conv=notrunc
```

Now patch the USBReadKeyData() method to read data from /.key (calling this function) instead of from the physical security key:

```
perl -e 'print "\x68\x9C\xDF\x28\x08\xC3"' | dd bs=1 count=6 seek=2383664 of=/usr/local/bin/start conv=notrunc
```

If you entered the commands properly so far, you should see the following with the md5sum command:

```
md5sum /usr/local/bin/start  
# Should return a321c5c22d9dee973b02d63fba4e5a96
```

Patching USBIO::GetDecryptVal()

In order for the program to read the /.key contents properly, we must also hardcode the decryption value.

The following patches the method to return that hard-coded value (assuming the output of `hexdump /.decrypt` was `1122 3344`):

```
perl -e 'print "\x55\x89\xE5\x8B\x45\x08"' | dd bs=1 count=6 seek=2386304 of=/usr/local/bin/start conv=notrunc  
perl -e 'print "\xC7\x80\x80\x03\x00\x00"' | dd bs=1 count=6 seek=2386310 of=/usr/local/bin/start conv=notrunc  
perl -e 'print "\x22\x11\x44\x33\x5D\xC3"' | dd bs=1 count=6 seek=2386316 of=/usr/local/bin/start conv=notrunc
```

Remember to replace `\x22\x11\x44\x33` with your specific value (eg: if your decrypt value was `7b8f 7a62`, then `\x22\x11\x44\x33` should be `\x8F\x7B\x62\x7A`).

Unfortunately, since the decryption value changes, we're unable to verify these changes via `md5sum`.

Patching USBIO::ReadKeyId()

Now we'll hard-code the key's serial ID into the binary, instead of having the binary read it from the key.

The steps below assume the serial key on the bottom of your physical key looks like the following:

11 88
22 33 44 55 66 77

First, make sure the hardcoded serial key is always used.

```
perl -e 'print "\xEB\x3B" | dd bs=1 count=2 seek=2382499 of=/usr/local/bin/start conv=notrunc
```

Second, add your hardcoded serial to the method.

```
perl -e 'print "\x56\x8B\x75\x0C\xC7\x06" | dd bs=1 count=6 seek=2382560 of=/usr/local/bin/start conv=notrunc  
perl -e 'print "\x88\x77\x66\x55" | dd bs=1 count=4 seek=2382566 of=/usr/local/bin/start conv=notrunc  
perl -e 'print "\xC7\x46\x04" | dd bs=1 count=3 seek=2382570 of=/usr/local/bin/start conv=notrunc  
perl -e 'print "\x44\x33\x22\x11" | dd bs=1 count=4 seek=2382573 of=/usr/local/bin/start conv=notrunc  
perl -e 'print "\x5E\x90\x90\x90" | dd bs=1 count=4 seek=2382577 of=/usr/local/bin/start conv=notrunc
```

Remember to replace `\x88\x77\x66\x55` and `\x44\x33\x22\x11` with your specific key's serial.

Confirm the game boots without the key

1. Make sure filesystem changes are made.

```
sync
```

2. Poweroff the machine.

3. Remove your key.

4. Turn the machine back on.

5. At the terminal, start the game.

```
/usr/local/bin/start
```

6. If the game menu selection screen appears, it's done! Follow the "Cleanup" instructions. Otherwise, follow the handling errors section.

Cleanup

1. Run the following commands:

```
cp ~/.xinitrc.bak ~/.xinitrc
```

```
cp /etc/passwd.bak /etc/passwd  
sync
```

2. Restart the machine.

Handling “Invalid key for version ...”, crashes, hangs, or other errors

It’s very likely there was a typo when issuing one of the many commands throughout this guide.

Restore the original “dstart” binary:

```
cp /usr/local/bin/dstart.bak /usr/local/bin/start  
chmod 4755 /usr/local/bin/start
```

Remove the added memory files:

```
rm /.key  
rm /.decrypt
```

To try the patching again, start over from the section with GDB. To restore the machine back to normal (requiring the key), go to the “Cleanup” section.